




**SERIES CAM-Ex  
SWITCH**  
CODE **292202EX**



### Datasheet

#### Specifications

Net Weight	779 G
Rated current	25A
Frequency	50/60Hz
Protection degree	IP66
Poles	3P
Rated operating voltage	500V~
Manufacturing material	Thermosetting halogen free
Width	92 mm
Execution	Wall mounting
Protection	None
Insulation Class	II
Dimensions	175X92X122 mm
Hole type	M25
Number of entries in enclosure	2
CAM layout	2
Function Apparatus Control	One way switches

#### Warranties, Reference Standards and Directives

Warranty	1 years
Certification and approval marks	CE, NYCE COLOMBIA, IECEx, TUV EX, EX
Directives	2014/34/EU (ATEX), 2014/35/EU (LVD), 2011/65/EU (RoHS), 2012/19/EU (WEEE)
Reference Standards	EN 60947-1:2007/A1:2011, EN 50581:2012, EN 63000:2018, EN 60947-3:2009, EN 60079 15:2010, EN 60947-3:2009/A1:2012, EN 60947-1:2007, EN 60079-0/A11:2013, EN 60079-0:2012, EN 60079-31:2014

#### Atex characteristics

ATEX application zone	Zona/Zone 2, 21 and 22
Dust Atex execution	II 2D - Ex tb IIIC T85 °C Db
Gas Atex execution	II 3G - Ex nR IIC T6/T5 Gc

The images are purely indicative. Palazzoli reserves the right to make changes without notice.