



SERIES TAIS-Ex
INTERLOCKED SOCKET
CODE 467146EX



Datasheet

Electrical characteristics

Rated current	16A
Supply Voltage	400V 50/60Hz ●
Poles	3P+N+ \perp
Clock Position	6h
Rated insulation voltage	500V
Insulation Class	II
Protection	None
Signal plug inserted	-

Technical data switch

Thermal current	16 A
Rated short-circuit current	10 kA
Terminals type	Screw - indirect clamping
Conductors section	Min: 1 mm ² ;Max: 10 mm ²
Terminal tightening torque	2 Nm
Auxiliary status contacts	-
Padlockable handle	-
Operating category	AC-23A / AC-3 16A - 415V

Mechanical characteristics

Manufacturing material	Thermosetting halogen free
Treatment type	-
Surface finishing	-
Color	Black RAL 9005
Width	125 mm
Execution	Wall mounting
Hole type	M25
Protection degree	IP66
Additional degree protection	-
Shock resistance	-
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Net Weight	2,676 G
Working Environment Temp.	Min: -40°C ;Max: +50°C/+65°C
Warehousing Temperature	Min: -50°C ;Max: +80°C

Atex characteristics

ATEX application zone	Zona/Zone 2, 21 and 22
Dust Atex execution	II 2D - Ex tb IIIC T90/T105 °C Db
Gas Atex execution	II 3G - Ex nR IIC T6/T5 Gc

Reference Standards and Directives

Certification and approval marks EX, IECEx, CE, TUV EX, NYCE COLOMBIA

Directives 2011/65/EU (RoHS), 2014/35/EU (LVD), 2012/19/EU (WEEE), 2014/34/EU (ATEX)

Reference Standards EN 60309-4:2007, EN 60309-4:2007/A1:2012, EN 60079-31:2014, EN 60079-0/A11:2013, EN 60309-1:1999/A1:2007, EN 50581:2012, EN 60309-1:1999/A2:2012, EN 60309 1:1999/A1AC:2014, EN 60079-15:2010, EN 63000:2018, EN 60309-1:1999, EN 60309 2:1999/A1:2007, EN 60079-0:2012, EN 60309 2:1999/A2:2012, EN 60309-2:1999

The images are purely indicative. Palazzoli reserves the right to make changes without notice.